

STAR RNAV RWY 03												
RMK	Senseur GNSS requis / GNSS Sensor required					MAG VAR 2020 0.8°E			REF NAV/VAID :			
	Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
BALAN 3M												
-	IF	BALAN	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL905	-	180	180.4	33.7	-	-	-	-	-	RNAV 1
-	TF	NERTI	-	198	198.6	16.0	-	3700	-	-	210	RNAV 1
GUERE 3M												
-	IF	GUERE	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL907	-	230	230.4	25.3	-	6000	-	-	-	RNAV 1
-	TF	SOLNO	-	229	230.1	28.0	-	3700	-	-	210	RNAV 1
GUSON 3M												
-	IF	GUSON	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL905	-	210	211.3	36.4	-	-	-	-	-	RNAV 1
-	TF	NERTI	-	198	198.6	16.0	-	3700	-	-	210	RNAV 1
MAKOX 3M												
-	IF	MAKOX	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL909	-	335	336.0	13.7	-	5000	-	-	-	RNAV 1
-	TF	MIGRA	-	335	335.9	9.4	-	3700	-	-	210	RNAV 1
NORON 3M												
-	IF	NORON	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL911	-	049	049.8	7.0	-	5000	-	-	-	RNAV 1
-	TF	MIGRA	-	049	049.9	11.6	-	3700	-	-	210	RNAV 1
PERIG 3M												
-	IF	PERIG	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL913	-	002	003.2	24.6	-	5000	-	-	-	RNAV 1
-	TF	MIGRA	-	002	003.3	9.5	-	3700	-	-	210	RNAV 1

