

RNP RWY 29												
RMK	MAG VAR 2020 0.8°E											REF NAV AID : NIL
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNIM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG		BX294	-	-	-	-	-	-	-	-	-	-
INA BX294	IF	BX294	Yes	-	-	-	-	-	5000	220	-	-
	DF	BX293	-	-	-	R	2300	2300	220	220	-	1.0
	TF	BX291	-	133	133.6	4.0	R	2300	2300	185	-	1.0
	TF	IBX29	-	223	223.7	4.0	-	2300	2300	185	-	1.0
INA BX291	IF	BX291	-	-	-	-	-	-	3500	185	-	-
	TF	IBX29	-	223	223.7	4.0	-	2300	2300	185	-	1.0
INA BX292	IF	BX292	-	-	-	-	-	-	4000	220	-	-
	TF	IBX29	-	309	309.9	5.0	-	2300	2300	185	-	1.0
	IF	IBX29	-	-	-	-	-	2300	2300	185	-	-
APCH	TF	FBX29	-	293	293.8	4.0	-	2300	2300	-	-	1.0
	TF	FW29	Yes	293	293.7	5.3	-	-	-	-	-3.40 / 49	0.3
	TF	BX290	Yes	293	293.6	3.5	-	-	2300	185	-	1.0
	DF	BX293	-	-	-	-	R	2300	2300	185	-	1.0
	TF	BX291	-	133	133.6	4.0	-	2300	2300	185	-	1.0