

ILS Z RWY 27													
RMK	Leg sequence	MAG VAR 2020 0.2°E						REF NAVAID :-					
		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
	HLDG	-	BZ277	-	-	-	-	-	-	-	-	-	-
	INA BZ277	IF	BZ277	-	-	-	-	-	-	220	-	-	-
		TF	BZ275	-	359	359.1	4.5	-	2500	3500	220	-	1.0
		TF	BZ276	-	089	089.2	7.0	R	2500	3500	220	-	1.0
		TF	IBZ27	-	189	189.5	4.6	R	2500	2500	200	-	1.0
	INA BZ274	IF	BZ274	-	-	-	-	-	2500	5000	-	-	-
		TF	BZ276	-	190	189.8	3.9	-	2500	3500	220	-	1.0
		TF	IBZ27	-	189	189.7	4.6	-	2500	2500	200	-	1.0
	INA BIDAC	IF	BIDAC	-	-	-	-	-	2500	5000	-	-	-
		TF	IBZ27	-	300	300.2	6.4	-	2500	2500	200	-	1.0
	INA BZ501	IF	BZ501	-	-	-	-	-	2500	3500	220	-	-
		TF	IBZ27	-	000	000.0	4.5	-	2500	2500	200	-	1.0
	APCH	IF	IBZ27	-	-	-	-	-	2500	2500	200	-	-

Voir carte / See chart ILS Z RWY 27