

RNP RWY 27														
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 0.2°E			REF NAV AID : -		
									MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)	
HLDG		-	BZ277	-	-	-	-	-	-	-	-	-	-	-
		IF	BZ277	-	-	-	-	-	-	3500	220	-	-	-
INA BZ277		TF	BZ275	-	359	359.1	4.5	-	-	3500	220	-	-	1.0
		TF	BZ276	-	089	089.2	7.0	R	-	3500	220	-	-	1.0
		TF	IBZ27	-	189	189.5	4.6	R	-	2500	200	-	-	1.0
		IF	BZ274	-	-	-	-	-	-	5000	-	-	-	-
INA BZ274		TF	BZ276	-	190	189.8	3.9	-	-	3500	220	-	-	1.0
		TF	IBZ27	-	189	189.7	4.6	-	-	2500	200	-	-	1.0
		IF	BIDAC	-	-	-	-	-	-	5000	-	-	-	-
INA BIDAC		TF	IBZ27	-	300	300.2	6.4	-	-	2500	200	-	-	1.0
		IF	BZ501	-	-	-	-	-	-	3500	220	-	-	-
INA BZ501		TF	IBZ27	-	000	000.0	4.5	-	-	2500	200	-	-	1.0
		IF	IBZ27	-	-	-	-	-	-	2500	200	-	-	-
APCH		TF	FBZ27	-	269	269.4	3.8	-	-	2500	-	-	-	1.0
		TF	RW27	Yes	269	269.3	7.0	-	-	-	-	-3.00 / 49	-	0.3
		TF	BZ270	Yes	269	269.1	3.7	-	-	4000	200	-	-	1.0
		DF	BZ272	-	-	-	-	R	-	4000	200	-	-	1.0
		TF	BZ274	-	099	099.2	16.3	R	-	4000	220	-	-	1.0