

RNP RWY 09													
RMK	Leg sequence	MAG VAR 2020 1.2°E										REF NAVAID :	
		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG		-	RWY09	-	-	-	-	-	-	-	-	-	-
	IF	RWY09	-	-	-	-	-	-	4000	4000	200	-	-
INA RW09	TF	CI410	-	088	089.3	5.8	-	-	-	-	-	-	1.0
	TF	CI414	-	358	359.4	4.0	-	-	-	-	-	-	1.0
	TF	CI402	-	271	272.6	17.9	-	-	-	-	-	-	1.0
	TF	CI09	-	178	179.1	5.0	-	3500	-	-	-	-	1.0
INA CI402	IF	CI402	-	-	-	-	-	4000	-	200	-	-	-
	TF	CI09	-	178	179.1	5.0	-	3500	-	-	-	-	1.0
INA CI404	IF	CI404	-	-	-	-	-	4000	-	200	-	-	-
	TF	CI09	-	358	359.1	5.0	-	3500	-	-	-	-	1.0
INA CI09	IF	CI09	-	-	-	-	-	3500	-	200	-	-	-
	IF	CI09	-	-	-	-	-	3500	-	200	-	-	-
APCH	TF	FCI09	-	088	089.1	5.0	-	3000	3000	-	-	-	1.0
	TF	RW09	YES	088	089.2	7.1	-	-	-	-	-3.20/49	-	0.3
	TF	CI410	-	088	089.3	5.8	-	-	-	-	-	-	1.0
	TF	CI414	-	358	359.4	4.0	-	-	4000	160	-	-	1.0
	TF	CI402	-	271	272.6	17.9	-	-	-	-	-	-	1.0