

RNP RWY 12												
RMK	MAG VAR 2020 0.2°E											REF NAV/VAID :-
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	DN305	-	-	-	-	-	-	-	-	-	-
INA DN121	IF	DN121	-	-	-	-	-	2500	4100	185	-	-
	TF	IDN12	-	190	190.6	4.4	-	2500	2500	185	-	1.0
INA DN122	IF	DN122	-	-	-	-	-	2500	3800	185	-	-
	TF	IDN12	-	032	032.5	4.0	-	2500	2500	185	-	1.0
	IF	DN305	-	-	-	-	-	2500	3800	220	-	-
INA DN305	DF	DN124	-	-	-	-	-	2500	3800	185	-	1.0
	TF	DN122	-	304	304.1	6.8	-	2500	3800	185	-	1.0
	TF	IDN12	-	032	032.5	4.0	-	2500	2500	185	-	1.0
	IF	IDN12	-	-	-	-	-	2500	2500	185	-	-
	TF	FDN12	-	122	122.5	3.5	-	2500	2500	-	-	1.0
	TF	RW12	Yes	122	122.5	6.6	-	-	-	-	-3.40 / 49	0.3
APCH	TF	DN120	Yes	122	122.6	2.4	-	-	2500	185	-	1.0
	DF	DN124	-	-	-	-	R	2500	3800	185	-	1.0
	TF	DN122	-	304	304.1	6.8	-	2500	3800	185	-	1.0