

BASTIA PORETTA
STAR RNAV RWY 16

(Protégées pour / Protected for CAT A, B, C, D)

STAR RNAV RWY 16											
RMK	GNSS required						MAG VAR 2020 2,8°E			REF NAVAID : -	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
HLDG											
-	-	CAPCO	-	-	-	-	-	-	-	-	-
BREMO 1V											
-	IF	BREMO	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BTA	-	340	342.6	15.1	-	5200	-	-	RNAV 1
-	TF	KB600	-	030	032.7	16.8	-	-	-	-	RNAV 1
-	TF	INVAK	-	012	015.0	6.0	-	-	-	220	RNAV 1
-	TF	ALISO	-	282	285.1	5.1	L	-	-	-	RNAV 1
-	TF	CAPCO	-	192	195.1	5.0	L	5000	-	-	RNAV 1
DOBIM 1V											
-	IF	DOBIM	-	-	-	-	-	-	130	-	RNAV 1
-	TF	GIRAG	-	292	295.1	5.8	-	-	-	-	RNAV 1
-	TF	ALISO	-	193	195.9	4.2	L	-	-	220	RNAV 1
-	TF	CAPCO	-	192	195.1	5.0	-	5000	-	-	RNAV 1
LIBLO 1V											
-	IF	LIBLO	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BARIL	-	053	055.8	26.6	-	10500	-	-	RNAV 1
-	TF	BTA	-	053	056.2	8.0	-	5200	-	-	RNAV 1
-	TF	KB600	-	030	032.7	16.8	-	-	-	-	RNAV 1
-	TF	INVAK	-	012	015.0	6.0	-	-	-	220	RNAV 1
-	TF	ALISO	-	282	285.1	5.1	L	-	-	-	RNAV 1
-	TF	CAPCO	-	192	195.1	5.0	L	5000	-	-	RNAV 1
LIGUR 1V											
-	IF	LIGUR	-	-	-	-	-	-	-	-	RNAV 1
-	TF	TORTU	-	182	184.9	9.3	-	-	140	-	RNAV 1
-	TF	AKUTI	-	182	184.7	9.7	-	-	-	-	RNAV 1
-	TF	ALISO	-	119	121.4	34.3	-	-	-	220	RNAV 1
-	TF	CAPCO	-	192	195.1	5.0	L	5000	-	-	RNAV 1
MOULE 1V											
-	IF	MOULE	-	-	-	-	-	-	130	250	RNAV 1
-	TF	INVAK	-	352	354.9	17.1	-	-	-	220	RNAV 1
-	TF	ALISO	-	282	285.1	5.1	-	-	-	-	RNAV 1
-	TF	CAPCO	-	192	195.1	5.0	L	5000	-	-	RNAV 1
NIRDO 1V											
-	IF	NIRDO	-	-	-	-	-	-	240	-	RNAV 1
-	TF	EVIRI	-	098	100.7	29.0	-	-	-	-	RNAV 1
-	TF	ALISO	-	105	108.1	24.1	-	-	-	220	RNAV 1
-	TF	CAPCO	-	192	195.1	5.0	-	5000	-	-	RNAV 1
NORKA 1V											
-	IF	NORKA	-	-	-	-	-	-	140	-	RNAV 1
-	TF	ALISO	-	089	092.1	35.8	-	-	-	220	RNAV 1
-	TF	CAPCO	-	192	195.1	5.0	R	5000	-	-	RNAV 1