

RNP Z RWY 18													
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 2.1°E		REF NAV AID :		
									MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	Vertical angle (°) / TCH (m)	NAV Spec	
	HLDG	-	PIRUV	Yes	096	098.0	4	R	6500	FL090	210	-	RNP APCH
	INA COLLO	IF	COLLO	-	-	-	-	-	6500	6500	200	-	RNP APCH
		TF	IB18Z	-	175	176.6	5.0	-	5000	-	170	-	RNP APCH
	INA PIRUV	IF	PIRUV	-	-	-	-	-	6500	-	210	-	RNP APCH
		TF	LB403	-	096	098.0	4.5	-	6500	6500	185	-	RNP APCH
		TF	IB18Z	-	085	086.7	3.4	-	5000	-	170	-	RNP APCH
		IF	IB18Z	-	-	-	-	-	5000	-	170	-	RNP APCH
		TF	FB18Z	-	175	176.7	4.1	-	5000	5000	-	-	RNP APCH
		TF	MLB18	Yes	175	176.7	6.4	-	-	-	-	-4.46° / 14	RNP APCH
		TF	LB600	-	175	176.7	7.9	-	-	-	-	-	RNP APCH
	APCH	TF	LB601	-	255	256.7	4.5	-	-	-	175	-	RNP APCH
		TF	LB602	-	340	341.7	6.0	-	-	-	-	-	RNP APCH
		TF	KENZO	-	319	321.3	12.5	-	-	-	-	-	RNP APCH
		TF	GOVNA	-	006	008.0	5.1	-	-	-	-	-	RNP APCH
		TF	PIRUV	-	096	097.9	4.5	-	6500	6500	210	-	RNP APCH