

**CHAMBERY AIX LES BAINS**  
**SID RNAV RWY 18**  
(Protégés pour / Protected for CAT A, B, C)

SID RNAV RWY 18											
RMK	GNSS required						MAG VAR 2020 2.1°E			REF NAVAID : VOR-DME CBY	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
<b>VENAT 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB602	-	340	341.7	6.0	-	-	-	200	RNAV 1
-	TF	BANEK	-	030	032.2	10.3	-	-	-	-	RNAV 1
-	TF	VENAT	-	045	047.1	41.4	-	-	-	-	RNAV 1
<b>ODIKI 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB602	-	340	341.7	6.0	-	-	-	200	RNAV 1
-	TF	BANEK	-	030	032.2	10.3	-	-	-	-	RNAV 1
-	TF	LB623	-	045	047.1	20.9	-	FL130	-	-	RNAV 1
-	TF	ODIKI	-	131	132.9	6.2	-	FL150	-	220	RNAV 1
<b>ESAPI 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB602	-	340	341.7	6.0	-	-	-	200	RNAV 1
-	TF	BANEK	-	030	032.2	10.3	-	-	-	-	RNAV 1
-	TF	LB622	-	045	047.1	18.4	-	FL130	-	-	RNAV 1
-	TF	ESAPI	-	141	143.4	7.1	-	FL150	-	220	RNAV 1
<b>PAS 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB602	-	340	341.7	6.0	-	-	-	200	RNAV 1
-	TF	BANEK	-	030	032.2	10.3	-	-	-	-	RNAV 1
-	TF	PAS	-	011	013.2	23.9	-	-	-	-	RNAV 1
<b>PIRUV 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	BELUS	-	314	316.2	11.5	-	-	-	-	RNAV 1
-	TF	KENZO	-	344	346.3	7.3	-	-	-	-	RNAV 1
-	TF	GOVNA	-	006	008.0	5.1	-	-	-	-	RNAV 1
-	TF	PIRUV	-	096	097.9	4.5	-	-	FL090	210	RNAV 1
<b>MOKIP 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	RNAV 1
-	TF	MAXUS	-	338	340.4	8.2	-	-	-	-	RNAV 1
-	TF	DANBO	-	301	303.4	16.2	-	FL150	-	-	RNAV 1
-	TF	MOKIP	-	001	002.6	31.7	-	-	-	-	RNAV 1
<b>DANBO 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	RNAV 1
-	TF	MAXUS	-	338	340.4	8.2	-	-	-	-	RNAV 1
-	TF	DANBO	-	301	303.4	16.2	-	-	-	-	RNAV 1
<b>MEBAK 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	RNAV 1
-	TF	LSE	-	290	292.2	16.2	-	-	-	-	RNAV 1
-	TF	MEBAK	-	261	263.2	18.7	-	-	-	-	RNAV 1
<b>MURRO 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	RNAV 1
-	TF	LSE	-	290	292.2	16.2	-	-	-	-	RNAV 1
-	TF	MURRO	-	229	230.9	39.0	-	-	-	-	RNAV 1
<b>ROMAM 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	RNAV 1
-	TF	ROMAM	-	198	200.4	34.7	L	-	-	-	RNAV 1
<b>LTP 8R</b>											
-	CF	LB600	-	175	176.7	4.5	-	-	-	-	RNAV 1
-	TF	LB601	-	255	256.7	4.5	-	-	FL090	190	RNAV 1
-	TF	LB603	-	293	294.6	15.6	-	-	-	-	RNAV 1
-	TF	LTP	-	180	182.1	9.3	L	-	-	200	RNAV 1