

RNP Y RWY 26													
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NIM)	Turn direction	MAG VAR 2020 1.4°E		REF NAV AID :-		
									MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	Vertical angle (°) / TCH (m)	NAV Spec	
	HLDG	-	RIMOR	-	-	-	-	-	-	-	-	-	
	INA MUBBI	IF	MUBBI	-	-	-	-	-	7100	220	-	RNP APCH	
		TF	LC403	-	261	262.5	6.3	-	5000	-	-	RNP APCH	
	INA RIMOR	TF	ILC26	-	261	262.3	3.6	-	4000	220	-	RNP APCH	
		IF	RIMOR	-	-	-	-	-	6000	-	-	RNP APCH	
		TF	ILC26	-	171	172.2	12.2	-	4000	220	-	RNP APCH	
	INA AMDAS	IF	AMDAS	-	-	-	-	-	FL090	-	-	RNP APCH	
		TF	LC405	-	310	311.6	7.7	-	6200	-	-	RNP APCH	
	APCH	TF	ILC26	-	310	311.6	4.8	-	4000	220	-	RNP APCH	
		IF	ILC26	-	-	-	-	-	4000	220	-	RNP APCH	
	APCH	TF	FC26Y	-	261	262.2	5.0	-	4000	4000	-	RNP APCH	
		TF	RW26	yes	261	262.2	9.1	-	-	-	185	-3.0° / 15.2	RNP APCH
		DF	LC411	-	-	-	-	R	-	-	185	-	RNP APCH
		TF	RIMOR	-	056	057.4	14.1	-	4900	-	-	RNP APCH	

← ← ← ↑ ↑ ↑