

LYON SAINT EXUPERY
STAR RNAV RWY 35L-35R
(Protégées pour / Protected for CAT A, B, C, D)

STAR RNAV RWY 35L-35R											
RMK	GNSS required				MAG VAR 2015 1.1°E			REF NAVAI : LSE			
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
HLDG											
ARBON	-	-	-	-	-	-	-	-	-	-	-
GOMET	-	-	-	-	-	-	-	-	-	-	-
TALAR	-	-	-	-	-	-	-	-	-	-	-
RIPTU	-	-	-	-	-	-	-	-	-	-	-
MEZIN 7N											
-	IF	MEZIN	-	-	-	-	-	-	-	-	RNAV 1
-	TF	NELEN	-	070	070.9	18.7	-	FL120	FL140	-	RNAV 1
-	TF	ROLIR	-	070	071.1	10.4	-	FL070	-	-	RNAV 1
-	TF	ARBON	-	016	016.8	6.8	-	FL070	-	-	RNAV 1
PINED 7N											
-	IF	PINED	-	-	-	-	-	-	FL130	-	RNAV 1
-	TF	LL103	-	359	359.7	8.3	-	-	-	-	RNAV 1
-	TF	OSMAS	-	359	359.6	8.5	-	FL100	-	-	RNAV 1
-	TF	GOMET	-	344	345.1	5.0	-	FL100	-	-	RNAV 1
AMVAR 7N											
-	IF	AMVAR	-	-	-	-	-	-	FL150	-	RNAV 1
-	TF	LL101	-	259	260.4	9.5	-	-	-	-	RNAV 1
-	TF	LL102	-	259	260.1	3.0	-	-	-	-	RNAV 1
-	TF	OSMAS	-	259	260.1	5.5	-	FL100	-	-	RNAV 1
-	TF	GOMET	-	344	345.1	5.0	-	FL100	-	-	RNAV 1
MILPA 7N											
-	IF	MILPA	-	-	-	-	-	-	FL180	-	RNAV 1
-	TF	KUDUP	-	250	251.1	13.4	-	FL090	FL120	-	RNAV 1
-	TF	AMKEN	-	250	250.9	8.7	-	-	-	-	RNAV 1
-	TF	RIPTU	-	204	204.9	5.0	-	FL070	-	-	RNAV 1
MTL 7N											
-	IF	MTL	-	-	-	-	-	-	-	-	RNAV 1
-	TF	AMONI	-	003	004.2	30.8	-	FL120	FL140	-	RNAV 1
-	TF	ROLIR	-	003	004.2	6.5	-	FL070	-	-	RNAV 1
-	TF	ARBON	-	016	016.8	6.8	-	FL070	-	-	RNAV 1