

RNP Z RWY04													
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NIM)	Turn direction	MAG VAR 2020 2.1° E			REF NAV AID :	
									MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)		Vertical angle (°) / TCH (m)
	HLDG	-	SOCOF	Yes	242	244.0	2.5	R	6500	FL090	170	-	-
		-	PIRUV	Yes	096	098.0	4.0	R	6500	FL090	210	-	-
		IF	PIRUV	-	-	-	-	-	6500	7900	210	-	-
		TF	LP403	-	096	098.0	4.5	-	6500	6500	200	-	1.0
		TF	LP402	-	099	101.5	5.3	-	5000	5000	-	-	1.0
		TF	IP04Z	-	126	128.4	3.0	-	3900	-	185	-	1.0
		IF	COLLO	-	-	-	-	-	6500	7800	-	-	-
		TF	LP405	-	175	176.7	3.9	-	5000	6000	200	-	1.0
		TF	LP402	-	139	141.1	3.0	-	5000	5000	-	-	1.0
		TF	IP04Z	-	126	128.4	3.0	-	3900	-	185	-	1.0
		IF	TOLNA	-	-	-	-	-	-	FL080	-	-	-
		TF	LP404	-	036	038.4	4.0	-	6500	6500	-	-	1.0
		TF	IP04Z	-	036	038.5	6.0	-	3900	-	185	-	1.0
		IF	IP04Z	-	-	-	-	-	3900	-	185	-	-
		TF	FP04Z	-	036	038.5	3.7	-	3500	3500	-	-	1.0
		TF	RW04	Yes	036	038.5	5.3	-	-	-	-	-3.5° / 15	0.3
		TF	LP411	Yes	036	038.6	4.5	-	-	-	-	-	1.0
		DF	LP412	-	-	-	-	L	-	5000	160	-	1.0
		TF	SOCOF	Yes	199	201.6	5.0	-	6500	6500	-	-	1.0