

GRENOBLE ALPES ISERE
SID RNAV RWY 27
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 27											
RMK	GNSS seulement / only						MAG VAR 2020 1.95°E			REF NAV AID : LSE	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
ROMAM 8W											
-	CF	LS722	-	268	270.2	-	-	-	-	-	1.0
-	TF	ROMAM	-	178	180.0	15.6	-	-	-	-	1.0
REPSI 8W											
-	CF	LS722	-	268	270.2	-	-	-	-	-	1.0
-	TF	REPSI	-	283	284.6	38.7	-	-	-	-	1.0
BELEP 8W											
-	CF	LS722	-	268	270.2	-	-	-	-	-	1.0
-	TF	BELEP	-	299	301.0	50.5	-	-	-	-	1.0
RISOR 8W											
-	CA	-	-	268	270.2	-	-	1900	-	-	1.0
-	DF	LS721	-	-	-	-	L	-	-	220	1.0
-	TF	RISOR	-	062	064.2	26.2	-	FL130	-	-	1.0
BELUS 8W											
-	CA	-	-	268	270.2	-	-	1900	-	-	1.0
-	DF	LS721	-	-	-	-	L	-	-	220	1.0
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	1.0
-	TF	BELUS	-	028	030.2	12.9	-	-	FL120	-	1.0
PIRUV 8W											
-	CA	-	-	268	270.2	-	-	1900	-	-	1.0
-	DF	LS721	-	-	-	-	L	-	-	220	1.0
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	1.0
-	TF	MAXUS	-	350	351.9	17.3	-	-	-	-	1.0
-	TF	GOVNA	-	050	051.5	10.1	-	6500	-	210	1.0
-	TF	PIRUV	-	096	097.9	4.5	-	-	FL80	-	1.0
MOKIP 8W											
-	CA	-	-	268	270.2	-	-	1900	-	-	1.0
-	DF	LS721	-	-	-	-	L	-	-	220	1.0
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	1.0
-	TF	DANBO	-	327	328.5	30.5	-	FL150	-	-	1.0
-	TF	MOKIP	-	001	002.6	31.7	-	-	-	-	1.0
DANBO 8W											
-	CA	-	-	268	270.2	-	-	1900	-	-	1.0
-	DF	LS721	-	-	-	-	L	-	-	220	1.0
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	1.0
-	TF	DANBO	-	327	328.5	30.5	-	-	-	-	1.0