

RNP RWY 19												
RMK	REF NAVAID : -											
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)
HLDG	-	IKNAH	-	-	-	-	-	-	-	-	-	-
INA LUCMA	IF	LUCMA	-	-	-	-	-	3900	-	220	-	-
	TF	ILU19	-	186	187.8	3.0	-	3000	-	200	-	1.0
INA IKNAH	IF	IKNAH	-	-	-	-	-	4000	-	200	-	-
	TF	LU502	-	006	007.8	8.5	-	3500	-	200	-	1.0
	TF	ILU19	-	096	097.8	5.0	-	3000	-	200	-	1.0
APCH	IF	ILU19	-	-	-	-	-	3000	-	200	-	-
	TF	FLU19	-	186	187.8	4.0	-	3000	3000	-	-	1.0
	TF	RW19	Yes	186	187.8	7.6	-	-	-	-	-3.0° / 15.0	0.3
	TF	LU522	Yes	186	187.8	4.0	-	-	-	160	-	1.0
	DF	LU520	-	-	-	-	R	4000	-	200	-	1.0