

RNP Z RWY 33												
RMK	MAG VAR 2020 1,9°E							REF NAVID :-				
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG		MI421						4000	4000			
INA MI421	IF	MI421						2200	3000	200		RNAV 1 / RNP APCH
	TF	MI422		151	152.6	5.0		1700	2200	200		RNAV 1 / RNP APCH
	TF	MI423		151	152.6	5.7		1700	1800	200		RNAV 1 / RNP APCH
	TF	MI424		076	078.2	4.8		1700	1700	200		RNAV 1 / RNP APCH
INA MI424	TF	IMI33		356	358.0	3.0		1700	1700	200		RNAV 1 / RNP APCH
	IF	MI424						1700	1800	200		RNAV 1 / RNP APCH
	TF	IMI33		356	358.0	3.0		1700	1700	200		RNAV 1 / RNP APCH
	IF	IMI33						1700	1700	200		RNAV 1 / RNP APCH
APCH	TF	FMI33		336	337.7	4.0		1700	1700			RNP APCH
	TF	IMI33	Yes	336	337.7	4.9					-3,0 / 15	RNP APCH
	TF	MI428		336	337.7	5.0			3000	200		RNP APCH
	TF	MI429		246	247.6	7.2			3000	200		RNP APCH
	TF	MI421		150	152.5	5.2		4000	4000	200		RNP APCH