

PRECODING RNP D RWY 22L/22R

RNP D RWY 22L-22R													
RMK	(1) GNSS required						MAG VAR 2020 2,4°E				REF NAV AID :-		
	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG	-	NERAS	-	-	-	-	-	-	-	-	-	-	-
INA NERAS	IF	NERAS	-	-	-	-	-	-	-	-	-	-	RNAV 1 (1)/ RNP APCH
	TF	MN404	-	258	260.6	12.7	-	4000	-	-	-	-	RNAV 1 (1)/ RNP APCH
	TF	SOTOX	-	348	350.1	7.2	-	-	-	-	-	-	RNAV 1 (1)/ RNP APCH
	TF	NANAX	-	347	349.8	5.0	-	3000	-	200	-	-	RNAV 1 (1)/ RNP APCH
INA MUS	IF	MUS	-	-	-	-	-	FL80	-	-	-	-	RNAV 1 (1)/ RNP APCH
	TF	MN402	-	088	090.0	14.7	-	-	5000	-	-	-	RNAV 1 (1)/ RNP APCH
	TF	MN404	-	088	090.0	26.1	-	4000	-	-	-	-	RNAV 1 (1)/ RNP APCH
	TF	SOTOX	-	348	350.1	7.2	-	-	-	-	-	-	RNAV 1 (1)/ RNP APCH
	TF	NANAX	-	347	349.8	5.0	-	3000	-	200	-	-	RNAV 1 (1)/ RNP APCH
APCH	IF	NANAX	-	347	349.8	5.0	-	-	-	-	-	-	RNP APCH
	TF	FN22D	-	303	305.1	3.0	-	3000	3000	-	-	-	RNP APCH
	TF	MN22D	Yes	303	305.1	6.0	-	-	-	-	-3.0	-	RNP APCH
	DF	MN412	-	-	-	-	L	-	-	185	-	-	RNP APCH
	TF	MN404	-	114	116.2	11.7	-	-	-	-	-	-	RNP APCH
	TF	MN414	-	103	105.8	9.6	-	-	-	-	-	-	RNP APCH
	TF	NERAS	-	033	034.9	5.8	-	-	3000	-	-	-	RNP APCH

