

RNP RWY 30													
RMK	MAG VAR 2020 2.0°E						RefNAVAID :						
	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
HLDG		GEMKO											
INA GEMKO	IF	GEMKO	Yes						5000		185		RNP APCH
	TF	MQ400		297	299.0	2.1							RNP APCH
	TF	PIPAX		040	042.3	3.0							RNP APCH
	TF	MQ402		092	094.0	12.9							RNP APCH
	TF	MQ404		092	093.6	4.0			5000				RNP APCH
	TF	IMQ30		170	171.9	5.0			3700		165		RNP APCH
INA PIPAX	IF	PIPAX											RNP APCH
	TF	MQ402		092	094.0	12.9					185		RNP APCH
	TF	MQ404		092	093.6	4.0			5000				RNP APCH
	TF	IMQ30		170	171.9	5.0			3700		165		RNP APCH
	IF	IMQ30							3700		165		RNP APCH
APCH	TF	FMQ30		260	262.0	4.0			3400				RNP APCH
	TF	MMQ30	Yes	290	291.9	5.0						-3.24 /15	RNP APCH
	DF	GEMKO					L		5000		185		RNP APCH