

RNP RWY 28												
RMK	MAG VAR 2020 1.6°E							REF NAV AID : -				
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG	-	OKBUK	-	-	-	-	-	-	-	-	-	-
INA VAXED	IF	VAXED	-	-	-	-	-	3500	4000	-	-	RNP APCH
	TF	OK404	-	102	103.6	14.6	-	3500	4000	-	-	RNP APCH
	TF	IOK28	-	190	191.5	5.0	-	2500	4000	210	-	RNP APCH
	IF	OKBUK	-	-	-	-	-	3500	-	-	-	RNP APCH
INA OKBUK	TF	VAXED	-	067	068.3	10.4	-	3500	4000	-	-	RNP APCH
	TF	OK404	-	102	103.6	14.6	-	3500	4000	-	-	RNP APCH
	TF	IOK28	-	190	191.5	5.0	-	2500	4000	210	-	RNP APCH
	IF	IOK28	-	-	-	-	-	2500	4000	210	-	RNP APCH
APCH	TF	FOK28	-	280	281.4	4.0	-	2500	2500	-	-	RNP APCH
	TF	RW28	Yes	280	281.4	5.9	-	-	-	-	-3.0 / 15.0	RNP APCH
	TF	OKBUK	-	280	281.2	13.5	-	-	2500	-	-	RNP APCH