

**MELUN VILLAROCHE  
PRECODING /INA RNAV RWY 28**

<b>INA RNAV RWY 28</b>														
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2015 0.3°E			REF NAV AID :-		
									MNIM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec	
	HLDG	-	MLN	-	-	-	-	-	-	-	-	-	-	-
	INA BRY	IF	BRY	-	-	-	-	-	-	2000	FL050	220 MAX	-	RNP APCH
		TF	PM501	-	313	313.0	11.1	-	-	2000	-	220 MAX	-	RNP APCH
		TF	IPM28	-	285	285.6	8.4	-	-	2000	-	170 MAX	-	RNP APCH
	INA NERIN	IF	NERIN	-	-	-	-	-	-	2000	-	170 MAX	-	RNP APCH
		TF	IPM28	-	213	213.7	5.0	-	-	2000	-	170 MAX	-	RNP APCH
	INA MLN	IF	MLN	-	-	-	-	-	-	2000	-	170 MAX	-	RNP APCH
		TF	PM500	-	048	048.1	4.6	-	-	2000	-	170 MAX	-	RNP APCH
		TF	IPM28	-	353	353.7	3.9	-	-	2000	-	170 MAX	-	RNP APCH
	INA VANEX	IF	VANEX	-	-	-	-	-	-	2000	-	170 MAX	-	RNP APCH
		TF	IPM28	-	285	285.5	3.7	-	-	2000	-	170 MAX	-	RNP APCH

