

**LILLE LESQUIN**  
**SID RNAV RWY 26**  
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 26											
RMK							MAG VAR 2020 1.2° E	REF NAVAIID : LEQ			
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
<b>ABB 6L</b>											
-	CF	QQ700	Yes	270	271.0	2.9	-	-	-	-	1.0
-	CF	QQ709	-	237	238.0	10.3	L	-	-	-	1.0
-	TF	OBIVA	-	209	210.1	20.4	-	-	-	-	1.0
-	TF	ABB	-	262	263.6	25.3	-	-	-	-	1.0
<b>BNE 6L</b>											
-	CF	QQ700	Yes	270	271.0	2.9	-	-	-	-	1.0
-	TF	IBERU	-	274	275.6	21.0	-	-	-	-	1.0
-	TF	BNE	-	274	274.8	21.1	-	-	-	-	1.0
<b>CIV 6L</b>											
-	CF	QQ700	Yes	270	271.0	2.9	-	-	-	-	1.0
-	CF	QQ703	-	#VALEURI!	AIP	AD 2 LFAQQ DATA SID RWY26	-	-	-	-	1.0
-	TF	QQ707	-	#VALEURI!	FRANCE	44728.0	-	-	-	-	1.0
-	TF	DENIN	-	101	102.2	15.5	-	-	-	-	1.0
-	TF	CIV	-	050	051.4	19.7	-	-	-	-	1.0
<b>MATIX 6L</b>											
-	CF	QQ700	Yes	270	271.0	2.9	-	-	-	-	1.0
-	CF	QQ703	-	206	207.0	5.9	L	-	-	-	1.0
-	TF	QQ707	-	129	130.0	5.8	-	-	-	-	1.0
-	TF	DENIN	-	101	102.2	15.5	-	-	-	-	1.0
-	TF	MATIX	-	130	131.0	24.8	-	-	-	-	1.0
<b>TRACA 6L</b>											
-	CF	QQ700	Yes	270	271.0	2.9	-	-	-	-	1.0
-	TF	IBERU	-	274	275.6	21.0	-	-	-	-	1.0
-	TF	TRACA	-	308	309.6	24.1	-	-	-	-	1.0
<b>VERMA 6L</b>											
-	CF	QQ700	Yes	270	271.0	2.9	-	-	-	-	1.0
-	CF	QQ703	-	206	207.0	5.9	L	-	-	-	1.0
-	TF	QQ713	-	173	174.6	13.5	-	-	-	-	1.0
-	TF	VERMA	-	143	144.4	19.4	-	-	-	-	1.0

SID RNAV RWY 26											
RMK	(1) FA ou/ou VA acceptable						MAG VAR 2020 1.2° E	REF NAVAIID : LEQ			
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
<b>CIV 6K</b>											
-	CA (1)	-	-	256	257.4	-	-	556 (400 AAL)	-	-	1.0
-	CF	QQ701	-	203	204.0	3.4	L	-	-	-	1.0
-	TF	DENIN	-	119	120.3	17.5	-	-	-	-	1.0
-	TF	CIV	-	050	051.4	19.7	-	-	-	-	1.0
<b>MATIX 6K</b>											
-	CA (1)	-	-	256	257.4	-	-	556 (400 AAL)	-	-	1.0
-	CF	QQ701	-	203	204.0	3.4	L	-	-	-	1.0
-	TF	DENIN	-	119	120.3	17.5	-	-	-	-	1.0
-	TF	MATIX	-	130	131.0	24.8	-	-	-	-	1.0
<b>VERMA 6K</b>											
-	CA (1)	-	-	256	257.4	-	-	556 (400 AAL)	-	-	1.0
-	CF	QQ701	-	203	204.0	3.4	L	-	-	-	1.0
-	TF	QQ711	-	179	179.8	15.3	-	-	-	-	1.0
-	TF	VERMA	-	152	153.4	17.7	-	-	-	-	1.0