

RNP RWY 10													
RMK	Leg sequence	MAG VAR 2020 0.2°W						REF NAV AID :					
		Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	RNP value
	HLDG	-	ENOKI	-	-	-	-	-	-	-	-	-	-
	INA RN504	IF	RN504	-	-	-	-	-	-	-	-	-	-
		TF	IFRN10	-	191	190.5	5.5	-	2000	-	-	-	1.0
	INA RN503	IF	RN503	-	-	-	-	-	-	-	-	-	-
		TF	IFRN10	-	101	100.5	3.0	-	2000	-	-	-	1.0
		IF	ENOKI	-	-	-	-	-	-	-	-	-	-
	INA ENOKI	TF	RN500	-	302	301.3	24.0	-	4000	-	-	-	1.0
		TF	RN502	-	281	280.6	4.0	-	4000	-	-	-	1.0
		TF	IFRN10	-	011	010.5	5.5	-	2000	-	-	-	1.0
	INA RN502	IF	RN502	-	-	-	-	-	4000	-	-	-	-
		TF	IFRN10	-	011	010.5	5.5	-	2000	-	-	-	1.0
		IF	IFRN10	-	-	-	-	-	2000	-	-	-	-
		TF	FRN10	-	101	100.5	4.6	-	2000	2000	-	-	1.0
	APCH	TF	RW10	Yes	101	100.5	5.9	-	-	-	-3.0°/50	-	0.3
		TF	RN510	Yes	101	100.7	3.0	-	-	-	-	-	1.0
		DF	RN500	-	-	-	-	R	-	200	-	-	1.0
		TF	RN502	-	281	280.6	4.0	-	4000	-	-	-	1.0