

TABLEAU POUR LES INTEGRATEURS DE DONNEES

Table for data integrators

RNP RWY 22														
RIMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 0.5°W			REF NAV AID :		
									MINI Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec	
	HLDG	-	VANEG	-	-	-	-	-	-	-	-	-	-	-
	INA VANEG	IF	VANEG	-	-	-	-	-	2200	-	-	-	-	RNP APCH
		TF	RV202	-	344	343.5	7.3	-	-	-	210	-	-	RNP APCH
	INA RV202	TF	IRV22	-	310	309.3	5.0	-	-	210	-	-	-	RNP APCH
		IF	RV202	-	-	-	-	-	-	-	210	-	-	RNP APCH
	INA RV204	TF	IRV22	-	310	309.3	5.0	-	-	210	-	-	-	RNP APCH
		IF	RV204	-	-	-	-	-	2400	-	210	-	-	RNP APCH
	INA IRV22	TF	IRV22	-	130	129.3	5.0	-	-	210	-	-	-	RNP APCH
		IF	IRV22	-	-	-	-	-	-	-	210	-	-	RNP APCH
	APCH	IF	IRV22	-	-	-	-	-	-	-	-	-	-	RNP APCH
		TF	FRV22	-	220	219.3	4.0	-	2100	2100	-	-	-	RNP APCH
		TF	RW22	YES	220	219.3	4.3	-	-	-	-	-3,5/15,0	-	RNP APCH
		TF	RV210	YES	220	219.2	2.0	-	-	-	-	-	-	RNP APCH
		DF	VANEG	-	-	-	-	L	2300	200	-	-	-	RNP APCH