

RNP RWY 26														
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020		2,1°E	REF NAV AID :-		
									MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)		Vertical angle (°) / TCH (m)	NAV Spec	
	HLDG	-	EMT	Yes	-	-	-	-	-	-	-	-	-	-
	INA SG402	IF	SG402	-	-	-	-	-	-	3000	-	-	-	RNAV 1 / RNP APCH
		TF	ISG26	-	353	354.6	5.0	-	-	3000	-	-	-	RNAV 1 / RNP APCH
	INA SG403	IF	SG403	-	-	-	-	-	-	3000	-	-	-	RNAV 1 / RNP APCH
		TF	ISG26	-	173	175.5	5.0	-	-	3000	-	-	-	RNAV 1 / RNP APCH
		IF	ISG26	-	-	-	-	-	-	3000	-	-	-	RNAV 1 / RNP APCH
		TF	EMT	-	263	265.1	6.7	R	-	3000	-	-	-	RNAV 1 / RNP APCH
	INA ISG26	TF	SG411	-	353	355.1	5.0	R	-	3000	220	-	-	RNAV 1 / RNP APCH
		TF	SG403	-	83	84.9	6.7	R	-	3000	-	-	-	RNAV 1 / RNP APCH
		TF	ISG26	-	173	175.5	5.0	-	-	3000	-	-	-	RNAV 1 / RNP APCH
		IF	ISG26	-	-	-	-	-	-	3000	-	-	-	RNP APCH
		TF	FSG26	-	263	265.3	5.0	-	-	3000	-	-	-	RNP APCH
	APCH	TF	RW26	Yes	263	265.2	6.0	-	-	-	-	-	-3.0 / 15	RNP APCH
		TF	SG409	Yes	263	265.0	3.0	L	-	-	-	-	-	RNP APCH
		DF	SG402	-	-	-	-	-	-	3000	200	-	-	RNP APCH

