

RNP RWY 05												
RMK	Fonctionnalité d'attente RNAV requise / RNAV holding functionality required								MAG VAR 2020	00.3°E	REF NAVAIID : BMC	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	ETPAR	Yes	165	165.0	4.6	L	5000/4000 if API	FL120	220	-	-
	-	VAGNA	Yes	225	225.0	4.6	L	5000	FL120	220	-	-
	-	LIBRU	Yes	260	260.0	4.6	L	5000	FL120	220	-	-
	-	DIRAX	Yes	325	325.0	4.2	L	5000	FL090	220	-	-
→ INA ETPAR	IF	ETPAR	-	-	-	-	-	-	-	220	-	-
	TF	BD055	-	179	179.5	16.8	-	5000	-	220	-	1.0
	TF	BD053	-	223	223.0	6.0	-	4000	-	-	-	1.0
	TF	BD051	-	191	191.7	3.0	-	3000	4000	-	-	1.0
	TF	BDN05	-	139	139.2	3.3	-	3000	3000	-	-	1.0
	TF	IBD05	-	135	135.4	2.9	L	2000	3000	185	-	1.0
→ INA VAGNA 1	IF	VAGNA	-	-	-	-	-	-	-	220	-	-
	TF	BD057	-	277	276.8	10.9	-	-	-	-	-	1.0
	TF	BD055	-	223	223.5	16.5	-	5000	-	220	-	1.0
	TF	BD053	-	223	223.0	6.0	-	4000	-	-	-	1.0
	TF	BD051	-	191	191.7	3.0	-	3000	4000	-	-	1.0
	TF	BDN05	-	139	139.2	3.3	-	3000	3000	-	-	1.0
	TF	IBD05	-	135	135.4	2.9	L	2000	3000	185	-	1.0
→ INA VAGNA 2 on ATC instruction	IF	VAGNA	-	-	-	-	-	-	-	220	-	-
	TF	BD058	-	184	184.4	12.1	-	-	-	-	-	1.0
	TF	BD056	-	223	223.2	16.0	-	-	-	-	-	1.0
	TF	BD054	-	223	223.1	4.0	-	5000	-	220	-	1.0
	TF	BD052	-	276	276.6	4.7	-	3000	4000	-	-	1.0
	TF	BDS05	-	315	315.2	2.1	-	3000	3000	-	-	1.0
	TF	IBD05	-	315	315.4	2.9	R	2000	3000	185	-	1.0
→ INA LIBRU	IF	LIBRU	-	-	-	-	-	-	-	220	-	-
	TF	BD058	-	272	272.6	7.2	-	-	-	-	-	1.0
	TF	BD056	-	223	223.2	16.0	-	-	-	-	-	1.0
	TF	BD054	-	223	223.1	4.0	-	5000	-	220	-	1.0
	TF	BD052	-	276	276.6	4.7	-	3000	4000	-	-	1.0
	TF	BDS05	-	315	315.2	2.1	-	3000	3000	-	-	1.0
	TF	IBD05	-	315	315.4	2.9	R	2000	3000	185	-	1.0
→ INA DIRAX	IF	DIRAX	-	-	-	-	-	-	-	220	-	-
	TF	BD054	-	301	301.8	11.3	-	5000	-	220	-	1.0
	TF	BD052	-	276	276.6	4.7	-	3000	4000	-	-	1.0
	TF	BDS05	-	315	315.2	2.1	-	3000	3000	-	-	1.0
	TF	IBD05	-	315	315.4	2.9	R	2000	3000	185	-	1.0
APCH	IF	IBD05	-	-	-	-	-	2000	3000	185	-	-
	TF	FBD05	-	045	045.4	3.5	-	2000	2000	-	-	1.0
	TF	RW05	Yes	045	045.4	5.0	-	-	-	-	-3.4°/ 49	0.3
	TF	BD050	Yes	045	045.5	3.0	-	-	4000	220	-	1.0
	TF	ETPAR	-	339	339.1	22.0	-	-	-	-	-	1.0