

BORDEAUX MERIGNAC
STAR RNAV RWY ALL

STAR RNAV RWY ALL													
RMK	GNSS ou/ou DME/DME (* basée sur le concept CDO/ based on CDO concept								MAG VAR 2020	0.3°E	REF NAVAID : BMC		
Procedure Identification	Path Terminator	Waypoint Identification	DTG THR23 (NM)	DTG THR29 (NM)	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
HLDG													
ETPAR	-	ETPAR	-	-	Yes	165	165	4.6	L	5000/4000 if API	FL120	220	RNAV1
VAGNA	-	VAGNA	-	-	Yes	225	225	4.6	L	5000	FL120	220	RNAV1
LIBRU	-	LIBRU	-	-	Yes	260	260	4.6	L	5000	FL120	220	RNAV1
DIRAX	-	DIRAX	-	-	Yes	325	325	4.2	L	5000	FL090	220	RNAV1
ROYAN 1L													
-	IF	ROYAN	-	-	-	-	-	-	-	-	FL150	-	RNAV1
-	TF	ETPAR	-	-	-	165	165.3	29.2	-	5000	FL120	-	RNAV1
CNA 1L (*)													
-	IF	CNA	57.7	68.8	-	-	-	-	-	-	FL200	-	RNAV1
-	TF	BD011	46.7	57.8	-	173	173.4	11.0	-	FL080	-	-	RNAV1
-	TF	BD002	28.1	39.2	-	173	173.4	18.6	-	-	-	-	RNAV1
-	TF	VAGNA	21.8	32.9	-	225	225.6	6.3	-	5000	FL120	-	RNAV1
LMG 1L (*)													
-	IF	LMG	93.8	104.9	-	-	-	-	-	-	-	-	RNAV1
-	TF	MARRE	55.1	66.2	-	234	234.1	38.7	-	FL200	FL240	-	RNAV1
-	TF	CHALA	47.1	58.2	-	233	233.5	8.0	-	FL160	FL190	-	RNAV1
-	TF	BD001	39.1	50.2	-	234	234.0	8.0	-	-	-	-	RNAV1
-	TF	BD002	28.1	39.2	-	234	233.9	11.0	-	-	-	-	RNAV1
-	TF	VAGNA	21.8	32.9	-	225	225.6	6.3	-	5000	FL120	-	RNAV1
VELIN 1L (*)													
-	IF	VELIN	43.5	40.5	-	-	-	-	-	-	FL150	-	RNAV1
-	TF	LIBRU	27.8	24.8	-	250	165.3	15.7	-	5000	FL120	-	RNAV1
MIRBA 1L (*)													
-	IF	MIRBA	52,0	-	-	-	-	-	-	-	FL170	-	RNAV1
-	TF	LIBRU	27.8	24.8	-	294	294.4	24.2	-	5000	FL120	-	RNAV1
VAVIX 1L (*)													
-	IF	VAVIX	-	45,0	-	-	-	-	-	-	FL150	-	RNAV1
-	TF	DIRAX	-	25.6	-	032	032.0	19.4	-	5000	FL090	-	RNAV1