

BORDEAUX MERIGNAC
SID RNAV RWY 29
Protégés pour / Protected for CAT A, B, C, D

| SID RNAV RWY 29 | | | |
|---|---|-----------------------------------|--|
| CAT | A B C D | | |
| PBN Box | RNAV 1 - senseur GNSS requis / GNSS sensor required | | |
| Climb gradient | <p>Les pentes théoriques de montée sont applicables aux départs omnidirectionnels et aux SID RNAV et conventionnels pour RWY29. <i>The theoretical climb gradients apply to omnidirectional departures and RNAV and conventional SID for RWY29.</i></p> <p>Pente théorique de montée 7.7% MNM jusqu'à 500 AAL. Obstacle pénalisant : bosquet de 220 ft AMSL situé à 225 m de la DER et à 130 m à gauche de l'axe de piste. Cette pente fait abstraction de la végétation de 241 ft AMSL à 150 m de la DER et à 130 m à gauche de l'axe et de la végétation de 231 ft AMSL à 200 m de la DER à 180 m à droite de l'axe de piste. <i>Theoretical climb gradient 7.7% MNM until 500 AAL. Most penalizing obstruction : copse 220 ft located at 225 m from the DER and 130 m on the left hand side of the axis. This slope doesn't take into account the 241 ft AMSL vegetation located 150 m from the DER 130 m left on the RWY axis, and the 231 ft AMSL vegetation located 200 m from the DER 180 m right of RWY axis.</i></p> | | |
| General RMK | Les waypoints soulignés sont des WP "à survoler" / <i>Underlined waypoints are "flyover" WP</i> | | |
| | | | |
| SID | Itinéraires / Routes | Clr Initiale Initial clearance | RMK |
| ROYAN 5R DME critique/ Critical DME : NIL | A la DER, monter RM 296°. A 500 ft AAL, virer à droite direct vers BD923 puis BD927 et ROYAN. <i>From the DER, climb MAG 296°. At 500 ft AAL, turn right direct to BD923 then BD927 and ROYAN.</i> | FL 070 | NIL |
| CNA 5R DME critique/ Critical DME : NIL | A la DER, monter RM 296°. A 500 ft AAL, virer à droite direct vers BD923 puis NB et CNA. <i>From the DER, climb MAG 296°. At 500 ft AAL, turn right direct to BD923 then NB and CNA.</i> | FL 070 | NIL |
| SAU 5R DME critique/ Critical DME : NIL | A la DER, monter RM 276°. A 500 ft AAL, virer à gauche direct vers BD929 puis vers BD935 et SAU. <i>From the DER, climb MAG 276°. At 500 ft AAL, turn left direct to BD929 then BD935 and SAU.</i> | FL 070 | 8.0% (5000 ft AMSL MNM 4 NM before BD935) |
| VAVIX 5R DME critique/ Critical DME : NIL | A la DER, monter RM 276°. A 500 ft AAL, virer à gauche direct vers BD929 puis vers VAVIX. <i>From the DER, climb MAG 276°. At 500 ft AAL, turn left direct to BD929 then VAVIX.</i> | FL 070 | NIL |

| Omnidirectional departures RWY 29 |
|--|
| Voir / see AD 2 LFBD SID RWY11-29 CONV -INSTR 01 |