

RNP RWY 21												
RMK	MAG VAR 2020 0.8°E						REF NAV AID :					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMI Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG	-	IBL21	-	-	-	-	-	-	-	-	-	-
INA BL502	IF	BL502	-	-	-	-	-	4000	-	220	-	RNP APCH
	TF	IBL21	-	122	123.2	5	-	4000	-	185	-	RNP APCH
INA BL504	IF	BL504	-	-	-	-	-	4000	-	220	-	RNP APCH
	TF	IBL21	-	302	303.3	5	-	4000	-	185	-	RNP APCH
APCH	IF	IBL21	-	-	-	-	-	4000	-	185	-	RNP APCH
	TF	FBL21	-	213	213.4	3.7	-	4000	4000	-	-	RNP APCH
	TF	RW21	Yes	213	213.3	8.4	-	-	-	-	-3.0/16.5	RNP APCH
	TF	BL512	Yes	212	213.3	2.1	-	-	-	-	-	RNP APCH
	DF	IBL21	-	-	-	-	R	-	4000	185	-	RNP APCH

←