

STAR RNAV RWY 21												
RMK	Senseur GNSS requis / GNSS Sensor required						MAG VAR 2020 0.8°E			REF NAV/VD :		
	Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NIM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
<b>BALAN 3R</b>												
-	IF	BALAN	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	IBL21	-	155	155.4	31.5	-	4000	-	185	-	RNAV 1
<b>GUERE 3R</b>												
-	IF	GUERE	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL703	-	253	253.9	22.8	-	6000	-	-	-	RNAV 1
-	TF	IBL21	-	253	253.5	9.5	-	4000	-	185	-	RNAV 1
<b>GUSON 3R</b>												
-	IF	GUSON	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	IBL21	-	191	191.8	26.7	-	4000	-	185	-	RNAV 1
<b>MAKOX 3R</b>												
-	IF	MAKOX	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL707	-	352	353.3	14.5	-	5000	-	-	-	RNAV 1
-	TF	BL504	-	022	022.5	27.3	-	4000	-	220	-	RNAV 1
<b>NORON 3R</b>												
-	IF	NORON	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL705	-	033	033.8	26.5	-	5000	-	-	-	RNAV 1
-	TF	BL502	-	032	033.2	16.7	-	4000	-	220	-	RNAV 1
<b>PERIG 3R</b>												
-	IF	PERIG	-	-	-	-	-	-	-	-	-	RNAV 1
-	TF	BL705	-	002	003.2	44.1	-	5000	-	-	-	RNAV 1
-	TF	BL502	-	032	033.2	16.7	-	4000	-	220	-	RNAV 1