

TOULOUSE BLAGNAC
PRECODING FNA RNP RWY 32L

FNA RNP RWY 32L

RMK	MAG VAR 2020 01.0°E										REF NAVAID :		
	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-		SULIT	-	-	-	-	-	-	-	-	-	-
APCH	IF		IO32L	-	-	-	-	-	3000	-	-	-	-
	TF		FO32L	-	322	323.0	3.6	-	3000	3000	-	-	1.0
	TF		RW32L	Yes	322	323.0	7.7	-	-	-	-	-3.00 / 48	0.3
	TF		TOU	Yes	323	323.8	4.6	-	-	-	-	-	1.0
	TF		BO614	-	303	304.0	10.0	-	-	4000	-	-	1.0
	TF		BO616	-	250	251.0	10.1	-	5000	-	-	-	1.0
	TF		BO618	-	165	166.4	13.9	-	-	-	-	-	1.0
	TF		SULIT	Yes	118	118.5	13.8	-	-	-	-	-	1.0