

PAU PYRENEES
SID RNAV RWY 31 (2V - 2Y)
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 31												
RMK	GNSS required						MAG VAR 2020 0.5°E			REF NAVAID : LMB		
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	MNM slope (%)	NAV Spec
←												
←												
←												
←												
←												
←												
←												
USAKU 2V												
-	CA	-	-	305	305.8	-	-	1281	-	205	9.5	RNAV1
-	DF	BP935	-	-	-	-	R	-	-	250	3.3	RNAV1
-	TF	DISIS	-	080	080.1	24.0	-	-	-	-	-	RNAV1
-	TF	USAKU	-	066	066.2	12.3	-	-	-	-	-	RNAV1
←												
←												
SOVOS 2V												
-	CF	BP931	Yes	305	305.8	3.5	-	-	-	205	4.3	RNAV1
-	TF	SOVOS	-	263	263.2	17.6	-	-	-	-	-	RNAV1
←												
←												
←												
←												
←												
←												
←												
←												
USAKU 2Y												
-	CF	BP931	Yes	305	305.8	3.5	-	-	-	205	4.3	RNAV1
-	DF	ARSIG	-	-	-	-	L	4000	-	250	3.3	RNAV1
-	TF	BP933	-	067	067.4	10.0	-	-	-	-	-	RNAV1
-	TF	LMB	-	061	061.2	10.9	-	-	-	-	-	RNAV1
-	TF	DISIS	-	066	066.0	11.1	-	-	-	-	-	RNAV1
-	TF	USAKU	-	066	066.2	12.3	-	-	-	-	-	RNAV1
←												
←												