

STAR RNAV RWY 27											
RMK	GNSS only					MAG VAR 2020 0.2°E			Ref NAVAIID : BTZ		
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Nav Spec
MAGEC 1S											
	IF	MAGEC							FL80		RNAV1
	TF	BZ274		190	190.0	8.4			5000*		RNAV1
	TF	BZ276		190	189.8	3.9		3000	3500*		RNAV1
	TF	IBZ27		190	189.7	4.6		3000		200	RNAV1
	TF	BZ		270	269.9	6.2		3000		220	RNAV1
SOVOS 1S											
	IF	SOVOS							FL100		RNAV1
	TF	BIDAC		280	280.1	10.5		3000	5000*		RNAV1
	TF	IBZ27		300	300.2	6.4		3000		200	RNAV1
	TF	BZ		270	269.9	6.2		3000		220	RNAV1
DONOS 1S											
	IF	DONOS							FL90		RNAV1
	TF	BZ503		019	18.9	7.0		3500	6000	220	RNAV1
	TF	BZ501		089	89.2	7.8		3000	3500*	220	RNAV1
	TF	IBZ27		000	000.0	4.5		3000		200	RNAV1
	TF	BZ		270	269.9	6.2		3000		220	RNAV1
SSN 1S											
	IF	SSN							FL90		RNAV1
	TF	BZ505		065	64.7	11.5		3500	6000		RNAV1
	TF	BZ503		089	89.1	6.7		3500	6000	220	RNAV1
	TF	BZ501		089	89.2	7.8		3000	3500*	220	RNAV1
	TF	IBZ27		000	000.0	4.5		3000		200	RNAV1
	TF	BZ		270	269.9	6.2		3000		220	RNAV1
* Restriction en cas d'arrivée directe autorisée											
HLDG	HF	BZ	yes	270	269.8	5.0	R	3000	FL70	220	RNAV1