

STAR RNAV RWY 31												
RMK	GNSS seulement / only					MAG VAR 2020 1.2°E			REF NAV AID :-			
	Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MINM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
BASLI 7M												
-	IF	BASLI	-	-	-	-	-	FL 080	FL 100	-	-	1.0
-	TF	OGALO	-	308	309.0	14.6	-	5200	-	210	-	1.0
ESISI 7M												
-	IF	ESISI	-	-	-	-	-	FL 210	FL 290	-	-	1.0
-	TF	RATRA	-	161	162.7	7.1	-	FL 190	FL 270	-	-	1.0
-	TF	CR217	-	124	125.2	44.3	-	FL 100	FL 130	-	-	1.0
-	TF	CR202	-	121	121.8	16.8	-	4700	-	220	-	1.0
GAI 7M												
-	IF	GAI	-	-	-	-	-	FL 140	FL 200	-	-	1.0
-	TF	CR218	-	066	67.0	10.9	-	FL 120	FL 160	-	-	1.0
-	TF	CR202	-	066	67.2	27.8	-	4700	-	220	-	1.0
MEN 7M												
-	IF	MEN	-	-	-	-	-	FL 110	FL 140	-	-	1.0
-	TF	CR215	-	222	223.7	12.0	-	FL 080	FL 110	-	-	1.0
-	TF	CR204	-	222	223.5	10.8	-	4900	-	220	-	1.0
MINPA 7M												
-	IF	MINPA	-	-	-	-	-	FL 170	FL 230	-	-	1.0
-	TF	CR216	-	198	199.4	34.6	-	FL 090	FL 120	-	-	1.0
-	TF	CR204	-	198	199.2	14.5	-	4900	-	220	-	1.0