

| FNA RNP RWY01 | | | | | | | | | | | | | | |
|---------------|--------------|-----------------|-------------------------|----------|-------------------|--------------------|---------------|----------------|-------------------------------|------------------------------|--------------|------------------------------|----------|----------|
| RMK | Leg sequence | Path Terminator | Waypoint Identification | Fly Over | Direction MAG (°) | Direction True (°) | Distance (NM) | Turn direction | MAG VAR 2020 02.5°E | | | REF NAV AID : | | |
| | | | | | | | | | MINM Altitude (FL or AMSL ft) | MAX Altitude (FL or AMSL ft) | MAX IAS (kt) | Vertical angle (°) / TCH (m) | NAV Spec | |
| - | | IF | IGA01 | - | | | | | 2500 | 3000 | 200 | | | RNP APCH |
| | APCH | TF | FGA01 | - | 009 | 011.0 | 4.0 | - | 2500 | - | - | | | RNP APCH |
| | | TF | RW01 | Y | 009 | 011.0 | 5.7 | - | - | - | - | -3/15 | | RNP APCH |
| | | TF | GA511 | Y | 009 | 011.0 | 4.0 | - | - | - | 200 | | | RNP APCH |
| | | DF | GA503 | - | | | | R | 2500 | 2500 | 200 | | | RNP APCH |
| | | TF | IGA01 | - | 279 | 281.0 | 5.0 | - | 2500 | 3000 | 200 | | | RNP APCH |