

CALVI SAINTE CATHERINE
STAR RNAV RWY 18
(Protégées pour / Protected for CAT A, B, C)

STAR RNAV RWY 18											
RMK	GNSS only						MAG VAR 2020 2.7°E			REF NAVAID :	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Navigation Accuracy (NM)
LIGUR 2K											
LIGUR	IF	-	-	-	-	-	-	-	-	-	1.0
TORTU	TF	-	-	182	185.1	9.4	-	-	FL140	-	1.0
AKUTI	TF	-	-	182	184.7	9.7	-	-	-	-	1.0
NORKA	TF	-	-	199	201.8	17.7	-	-	-	-	1.0
SOUKA	TF	-	-	177	179.6	3.8	-	-	-	-	1.0
BISKI	TF	-	-	177	180.0	6.8	-	3000	-	-	1.0
CAPCO 2K											
CAPCO	IF	-	-	-	-	-	-	-	-	-	1.0
MILNO	TF	-	-	278	280.7	16.3	-	6000	-	-	1.0
KC528	TF	-	-	266	268.8	10.0	-	-	-	-	1.0
SOUKA	TF	-	-	266	268.7	8.5	-	-	-	-	1.0
BISKI	TF	-	-	177	180.0	6.8	-	3000	-	-	1.0
SODRI 2K											
SODRI	IF	-	-	-	-	-	-	-	-	-	1.0
NORKA	TF	-	-	098	100.9	18.8	-	-	-	-	1.0
SOUKA	TF	-	-	177	179.6	3.8	-	-	-	-	1.0
BISKI	TF	-	-	177	180.0	6.8	-	3000	-	-	1.0
NIRDO 2K											
NIRDO	IF	-	-	-	-	-	-	-	-	-	1.0
NORKA	TF	-	-	124	126.2	19.5	-	-	-	-	1.0
SOUKA	TF	-	-	177	179.6	3.8	-	-	-	-	1.0
BISKI	TF	-	-	177	180.0	6.8	-	3000	-	-	1.0
LIBLO 2K											
LIBLO	IF	-	-	-	-	-	-	10500	-	-	1.0
KC520	TF	-	-	357	360.0	12.4	-	9100	-	-	1.0
KC522	TF	-	-	021	023.5	7.0	-	6700	-	-	1.0
KC524	TF	-	-	021	023.6	4.7	-	5000	-	-	1.0
KC526	TF	-	-	021	023.6	5.7	-	-	-	-	1.0
KC528	TF	-	-	357	359.9	10.2	-	-	-	-	1.0
SOUKA	TF	-	-	266	268.7	8.5	L	-	-	-	1.0
BISKI	TF	-	-	177	180.0	6.8	-	3000	-	-	1.0