

FIGARI SUD CORSE
PRECODING STAR RNAV (GNSS) RWY 05
(Protégées pour / Protected for CAT A, B, C)

STAR RNAV RWY 05											
RMK	GNSS required						MAG VAR 2020 2.7 °E			REF NAV AID : -	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
HLDG											
GALDA	-	-	-	-	-	-	-	-	-	-	-
BTA 2R											
-	IF	BTA	-	-	-	-	-	-	-	-	RNAV 1
-	TF	KF620	-	202	204.6	46.7	-	9800	-	-	RNAV 1
-	TF	KF610	-	202	204.4	12.0	-	6200	-	-	RNAV 1
-	TF	KF600	-	202	204.3	12.0	-	-	-	-	RNAV 1
-	TF	GALDA	-	146	148.3	5.0	-	4000	-	-	RNAV 1
TORTU 2R											
-	IF	TORTU	-	-	-	-	-	-	-	-	RNAV 1
-	TF	LIBLO	-	182	184.8	68.5	-	10700	-	-	RNAV 1
-	TF	VICCO	-	182	184.8	6.7	-	8600	-	-	RNAV 1
-	TF	AJO	-	182	184.8	22.2	-	6500	-	-	RNAV 1
-	TF	KF600	-	170	172.6	16.3	-	-	-	-	RNAV 1
-	TF	GALDA	-	146	148.3	5.0	-	4000	-	-	RNAV 1
LONSU 2R											
-	IF	LONSU	-	-	-	-	-	-	-	-	RNAV 1
-	TF	AJO	-	148	150.8	69.0	-	-	-	-	RNAV 1
-	TF	KF600	-	170	172.6	16.3	-	-	-	-	RNAV 1
-	TF	GALDA	-	146	148.3	5.0	-	4000	-	-	RNAV 1
VAREK 2R											
-	IF	VAREK	-	-	-	-	-	-	-	-	RNAV 1
-	TF	AJO	-	130	132.3	48.2	-	-	-	-	RNAV 1
-	TF	KF600	-	170	172.6	16.3	-	-	-	-	RNAV 1
-	TF	GALDA	-	146	148.3	5.0	-	4000	-	-	RNAV 1
RUBAS 2R											
-	IF	RUBAS	-	-	-	-	-	-	-	-	RNAV 1
-	TF	AJO	-	107	109.5	105	-	-	-	-	RNAV 1
-	TF	KF600	-	170	172.6	16.3	-	-	-	-	RNAV 1
-	TF	GALDA	-	146	148.3	5.0	-	4000	-	-	RNAV 1
NEGAT 2R											
-	IF	NEGAT	-	-	-	-	-	-	-	-	RNAV 1
-	TF	KF680	-	080	082.7	37.6	-	-	-	-	RNAV 1
-	TF	KF600	-	081	083.3	6.0	-	-	-	-	RNAV 1
-	TF	GALDA	-	146	148.3	5.0	-	4000	-	-	RNAV 1
POULP 2R											
-	IF	POULP	-	-	-	-	-	-	FL 120	-	RNAV 1
-	TF	KF680	-	027	029.9	10.7	-	-	-	-	RNAV 1
-	TF	KF600	-	081	083.3	6.0	-	-	-	-	RNAV 1
-	TF	GALDA	-	146	148.3	5.0	-	4000	-	-	RNAV 1
TEREZ 2R											
-	IF	TEREZ	-	-	-	-	-	-	FL 100	-	RNAV 1
-	TF	KF640	-	356	358.2	10.1	-	-	-	-	RNAV 1
-	TF	KF630	-	298	300.4	5.5	-	-	-	-	RNAV 1
-	TF	KF600	-	235	238.1	5.5	-	-	-	-	RNAV 1
-	TF	GALDA	-	146	148.3	5.0	-	4000	-	-	RNAV 1
ASKAG 2R											
-	IF	ASKAG	-	-	-	-	-	-	FL 100	-	RNAV 1
-	TF	KF630	-	246	248.9	39.9	-	6100	-	-	RNAV 1
-	TF	KF600	-	235	238.1	5.5	-	-	-	-	RNAV 1
-	TF	GALDA	-	146	148.3	5.0	L	4000	-	-	RNAV 1