

RNP Z RWY 26												
RMK							MAG VAR 2020 1.4°E			REF NAV AID : -		
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG	-	RIMOR	-	-	-	-	-	-	-	-	-	-
INA MUBBI	IF	MUBBI	-	-	-	-	-	7100	-	220	-	RNP APCH
	TF	LC403	-	261	262.5	6.3	-	5000	-	-	-	RNP APCH
	TF	ILC26	-	261	262.3	3.6	-	4000	-	220	-	RNP APCH
INA RIMOR	IF	RIMOR	-	-	-	-	-	6000	-	-	-	RNP APCH
	TF	ILC26	-	171	172.2	12.2	-	4000	-	220	-	RNP APCH
INA AMDAS	IF	AMDAS	-	-	-	-	-	FL 090	-	-	-	RNP APCH
	TF	LC405	-	310	311.6	7.7	-	6200	-	-	-	RNP APCH
	TF	ILC26	-	310	311.6	4.8	-	4000	-	220	-	RNP APCH
APCH	IF	ILC26	-	-	-	-	-	4000	-	220	-	RNP APCH
	TF	FC26Z	-	261	262.2	5.2	-	4000	4000	-	-	RNP APCH
	TF	LC409	yes	261	262.2	9.6	-	-	-	185	-3.0° / 15.2	RNP APCH
	DF	LC411	-	-	-	-	R	-	-	185	-	RNP APCH
	TF	RIMOR	-	056	057.4	14.1	-	4900	-	-	-	RNP APCH

↓ ↓ ↓ ↑ ↑ ↑