

RNP x RWY04														
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 2.1° E			REF NAVAID :		
									MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)	
	HLDG	-	SOCOF	-	-	-	-	-	-	-	-	-	-	-
		IF	SOCOF	-	-	-	-	-	-	100	-	-	-	-
	INA AT	TF	LP615	-	282	283.7	3.3	-	-	-	-	-	-	1.0
		TF	LP613	-	217	218.6	2.1	-	-	-	5000	-	-	1.0
		TF	IP04X	-	126	128.5	3.0	-	-	100	4500	-	-	1.0
	INA TOLNA	IF	TOLNA	-	-	-	-	-	-	-	FL080	-	-	-
		TF	LP404	-	036	038.4	4.0	-	-	-	6500	-	-	1.0
		TF	IP04X	-	036	038.5	6.5	-	-	100	4500	-	-	1.0
		IF	IP04X	-	-	-	-	-	-	100	4500	-	-	-
	APCH	TF	FP04X	-	036	038.5	4.1	-	-	-	3900	-	-	1.0
		TF	RW04H	YES	036	038.5	4.8	-	-	70	-	-4,6° / 10.7	-	0.3
		DF	SOCOF	-	-	-	-	R	-	70	6500	-	-	1.0