

RNP Y RWY 04													
RMK	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MAG VAR 2020 2.1° E			REF NAV AID :	
									MNIM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Navigation Accuracy (NM)
	HLDG	-	SOCOF	Yes	242	244.0	2.5	R	6500	FL090	170	-	-
	INA AT	IF	SOCOF						6500	FL080	190	-	-
		TF	LP409	-	257	259.0	5.3	-	5500	-	190	-	1.0
		TF	LP408	-	216	218.5	3.0	-	5000	-	190	-	1.0
		TF	IP04Y	-	126	128.4	3.5	-	4500	-	190	-	1.0
	APCH	IF	IP04Y						4500	-	190		-
		TF	FP04Y	-	036	038.5	4.0	-	4500	4500	-	-	1.0
		TF	RW04	Yes	036	038.5	8.0	-	-	-	-	-3.5° / 15	0.3
		TF	LP411	Yes	036	038.6	4.5	-	-	-	-	-	1.0
		DF	LP412	-	-	-	-	L	-	5000	160	-	1.0
		TF	SOCOF	Yes	199	201.6	5.0	-	6500	6500	-	-	1.0