

GRENOBLE ALPES ISERE
SID RNAV RWY 27
(Protégés pour / Protected for CAT A, B, C, D)

SID RNAV RWY 27											
RMK	GNSS required						MAG VAR 2020 1.95°E			REF NAVAID : LSE	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
ROMAM 6W											
-	CF	LS722	-	268	270.2	6.2	-	-	-	-	RNAV1
-	TF	ROMAM	-	178	180.0	15.6	-	-	-	-	RNAV1
REPSI 6W											
-	CF	LS722	-	268	270.2	6.2	-	-	-	-	RNAV1
-	TF	REPSI	-	283	284.6	38.7	-	-	-	-	RNAV1
BELEP 6W											
-	CF	LS722	-	268	270.2	6.2	-	-	-	-	RNAV1
-	TF	BELEP	-	299	301.0	50.5	-	-	-	-	RNAV1
RISOR 6W											
-	CA	-	-	268	270.2	-	-	1900	-	-	RNAV1
-	DF	LS721	-	-	-	-	L	-	-	220	RNAV1
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	RNAV1
-	TF	PENAR	-	080	082.2	8	-	FL100	-	-	RNAV1
-	TF	RISOR	-	080	082.3	14.3	-	FL130	-	-	RNAV1
SOPLO 6W											
-	CA	-	-	268	270.2	-	-	1900	-	-	RNAV1
-	DF	LS721	-	-	-	-	L	-	-	220	RNAV1
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	RNAV1
-	TF	SOPLO	-	040	041.8	19.3	-	-	FL140	-	RNAV1
BELUS 6W											
-	CA	-	-	268	270.2	-	-	1900	-	-	RNAV1
-	DF	LS721	-	-	-	-	L	-	-	220	RNAV1
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	RNAV1
-	TF	BELUS	-	028	030.2	12.9	-	-	FL120	-	RNAV1
PIRUV 6W											
-	CA	-	-	268	270.2	-	-	1900	-	-	RNAV1
-	DF	LS721	-	-	-	-	L	-	-	220	RNAV1
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	RNAV1
-	TF	MAXUS	-	350	351.9	17.3	-	-	-	-	RNAV1
-	TF	GOVNA	-	050	051.5	10.1	-	6500	-	210	RNAV1
-	TF	PIRUV	-	096	097.9	4.5	-	-	FL80	-	RNAV1
MOKIP 6W											
-	CA	-	-	268	270.2	-	-	1900	-	-	RNAV1
-	DF	LS721	-	-	-	-	L	-	-	220	RNAV1
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	RNAV1
-	TF	DANBO	-	327	328.5	30.5	-	FL150	-	-	RNAV1
-	TF	MOKIP	-	001	002.6	31.7	-	-	-	-	RNAV1
DANBO 6W											
-	CA	-	-	268	270.2	-	-	1900	-	-	RNAV1
-	DF	LS721	-	-	-	-	L	-	-	220	RNAV1
-	TF	LTP	-	008	010.0	8.5	-	-	-	-	RNAV1
-	TF	DANBO	-	327	328.5	30.5	-	-	-	-	RNAV1