

RNP Z RWY22L (AR)													
RMK	AUTHORIZATION REQUIRED						MAG VAP 2020 2.4°E			REF NAVAID : AZR			
	Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy
INA SOTOX	IF	SOTOX	-	-	-	-	-	-	-	-	-	-	1.0
	TF	NANAX	-	348	350.2	5.0	-	3000	-	240	-	-	1.0
	TF	IN22Z	-	303	305.1	5.2	-	2000	-	200	-	-	1.0
	IF	IN22Z	-	-	-	-	-	2000	-	200	-	-	1.0
	TF	F22LZ	-	303	305.1	3.0	-	2000	2000	-	-	-	1.0
APCH	TF	MN904	-	303	305.0	2.5	-	-	-	160	-	-3.2°/49	0.3
	RF Centre : CMN03 Rayon : 1.37		-	-	-	1.9	L	-	-	160	-	-3.2°/49	0.3
	TF	RW22L	Yes	223	224.9	1.3	-	-	-	-	-	-3.2°/49	0.3
	FM	RW22L	-	223	224.9	-	-	3000	3000	-	-	-	1.0
HLDG	-	NERAS	-	-	-	-	-	-	-	-	-	-	