

RNP RWY 25												
RMK								MAG VAR 2020 0.9°E			Ref NAV AID :	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
HLDG		OJ430										RNAV 1 / RNP APCH
HLDG		OJ433										RNAV 1 / RNP APCH
INA OJ430	IF	OJ430						2100		210		RNAV 1 / RNP APCH
	TF	OJ431		068	069.2	6.0						RNAV 1 / RNP APCH
	TF	IOJ25		159	159.5	4.0						RNAV 1 / RNP APCH
INA OJ432	IF	OJ432						2100		220		RNAV 1 / RNP APCH
	TF	IOJ25		249	249.5	5.5						RNAV 1 / RNP APCH
	IF	OJ433						4000		220		RNAV 1 / RNP APCH
INA OJ433	TF	OJ434		057	057.8	12.5		4000				RNAV 1 / RNP APCH
	TF	IOJ25		339	339.5	8.0		2100				RNAV 1 / RNP APCH
	IF	IOJ25						2100		220		RNP APCH
APCH	TF	FOJ25		249	249.5	5.0		2100	2100			RNP APCH
	TF	RW25	Yes	249	249.4	5.1					-3.0 / 15	RNP APCH
	TF	OJ435	Yes	249	249.4	3.0						RNP APCH
	DF	OJ430					R	2100	2100	185		RNP APCH