

**BLOIS LE BREUIL
PRECODING RNP RWY 12**

RNP RWY 12												
RMK	NIL	MAG VAR 2020				0.74E	Ref NAVAID :					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (ft)	Navigation Accuracy (NM)
HLDG	-	BABOG	-	-	-	-	-	-	-	-	-	-
INA OQ502	IF	OQ502	-	-	-	-	-	2100	2500	200	-	1.0
	TF	IOQ12	-	120	121.2	6.5	-	2100	-	200	-	1.0
INA BABOG	IF	BABOG	-	-	-	-	-	2500	4000	230	-	1.0
	TF	OQ505	-	342	343.1	10.4	-	-	-	-	-	1.0
	TF	OQ504	-	311	311.6	6.6	-	-	-	-	-	1.0
	TF	OQ503	-	306	306.3	13.5	-	2100	2500	200	-	1.0
	TF	OQ502	-	210	211.2	4.2	-	-	-	200	-	1.0
	TF	IOQ12	-	120	121.2	6.5	-	2100	-	200	-	1.0
INA OQ503	IF	OQ503	-	-	-	-	-	2100	2500	200	-	1.0
	TF	OQ502	-	210	211.2	4.2	-	-	-	200	-	1.0
	TF	IOQ12	-	120	121.2	6.5	-	2100	-	-	-	1.0
	IF	IOQ12	-	-	-	-	-	2100	-	-	-	1.0
APCH	TF	FOQ12	-	121	121.3	5.0	-	2100	2100	-	-	1.0
	TF	RW12	Yes	121	121.4	5.2	-	447	447	-	-3.0° / 50	0.3
	TF	OQ520	-	121	121.5	3.0	-	-	-	230	-	1.0
	TF	BABOG	Yes	153	153.4	9.5	-	2500	-	230	-	1.0
	HM	BABOG	Yes	31	32	T 1 min	L	2500	2500	230	-	-