

TOURS VAL DE LOIRE
SID RNAV RWY ALL
Protégés pour / Protected for CAT A, B, C, D

SID RNAV RWY 02											
RMK	(1) GNSS requis / required						MAG VAR 2020 0.6°E			REF NAV AID : CAD	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
OMARI 1N											
	CA	-	-	015	015.3	-	-	800	-	-	RNAV 1 (1)
	DF	OMARI	-	-	-	-	R	FL070	-	-	RNAV 1 (1)
SOPIL 1N											
	CA	-	-	015	015.3	-	-	800	-	-	RNAV 1 (1)
	DF	OMARI	-	-	-	-	R	FL070	-	-	RNAV 1 (1)
	TF	SOPIL	-	131	131.8	12.7	-	-	-	-	RNAV 1 (1)
VANAD 1N											
	CA	-	-	015	015.3	-	-	800	-	-	RNAV 1 (1)
	DF	VANAD	-	-	-	-	-	FL070	-	-	RNAV 1 (1)

SID RNAV RWY 20											
RMK	(1) GNSS requis / required						MAG VAR 2020 0.6°E			REF NAV AID : CAD	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
OMARI 1S											
	CA	-	-	195	195.3	-	-	800	-	-	RNAV 1 (1)
	CF	OT700	Yes	147	148.0	-	L	3000	-	-	RNAV 1 (1)
	TF	OT701	-	165	165.5	6.4	-	FL070	-	-	RNAV 1 (1)
	TF	OMARI	-	165	165.3	4.9	-	-	-	-	RNAV 1 (1)
SOPIL 1S											
	CA	-	-	195	195.3	-	-	800	-	-	RNAV 1 (1)
	CF	OT700	Yes	147	148.0	-	L	3000	-	-	RNAV 1 (1)
	TF	OT701	-	165	165.5	6.4	-	FL070	-	-	RNAV 1 (1)
	TF	OMARI	-	165	165.3	4.9	-	-	-	-	RNAV 1 (1)
	TF	SOPIL	-	131	131.8	12.7	-	-	-	-	RNAV 1 (1)
VANAD 1S											
	CA	-	-	195	195.3	-	-	800	-	-	RNAV 1 (1)
	CF	OT700	Yes	147	148.0	-	L	3000	-	-	RNAV 1 (1)
	DF	OT702	-	-	-	-	L	-	-	-	RNAV 1 (1)
	TF	OT703	-	006	006.9	9.4	-	-	-	-	RNAV 1 (1)
	TF	VANAD	-	359	359.3	14.0	-	FL070	-	-	RNAV 1 (1)