

TOURS VAL DE LOIRE
STAR RNAV RWY 02
Protégées pour / Protected for CAT A, B, C, D

STAR RNAV RWY 02											
RMK	(1) GNSS requis / required (2) Sur instruction du CTL / With ATC clearance						MAG VAR 2020 0.6°E			REF NAVAID : -	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	NAV Spec
HLDG											
-	-	OTKUR	-	-	-	-	-	-	-	-	-
POI 1A (2)											
	IF	POI	-	-	-	-	-	-	-	-	RNAV 1 (1)
	TF	OT801	-	031	031.5	20.6	-	-	-	-	RNAV 1 (1)
	TF	OT802	-	349	349.4	9.4	-	FL070	-	-	RNAV 1 (1)
	TF	OT804	-	349	349.3	9.1	-	5000	-	-	RNAV 1 (1)
	TF	OT452	-	349	349.3	4.8	-	-	-	-	RNAV 1 (1)
	TF	OTKUR	-	014	015.1	9.2	-	4000	-	-	RNAV 1 (1)
POI 1D (2)											
	IF	POI	-	-	-	-	-	-	-	-	RNAV 1 (1)
	TF	OT801	-	031	031.5	20.6	-	-	-	-	RNAV 1 (1)
	TF	OT802	-	349	349.4	9.4	-	FL070	-	-	RNAV 1 (1)
	TF	OT803	-	023	023.9	6.2	-	5000	-	-	RNAV 1 (1)
	TF	IOT02	-	023	024.0	6.5	-	3000	-	230	RNAV 1 (1)
OMARI 1A											
	IF	OMARI	-	-	-	-	-	-	-	-	RNAV 1 (1)
	TF	OT800	-	334	334.2	7.7	-	FL070	-	-	RNAV 1 (1)
	TF	OTKUR	-	307	307.9	11.9	-	4000	-	-	RNAV 1 (1)
SOPIL 1A											
	IF	SOPIL	-	-	-	-	-	-	-	-	RNAV 1 (1)
	TF	OMARI	-	311	311.9	12.7	-	-	-	-	RNAV 1 (1)
	TF	OT800	-	334	334.2	7.7	-	FL070	-	-	RNAV 1 (1)
	TF	OTKUR	-	307	307.9	11.9	-	4000	-	-	RNAV 1 (1)
VANAD 1A											
	IF	VANAD	-	-	-	-	-	-	-	-	RNAV 1 (1)
	TF	OT902	-	230	230.7	9.0	-	5000	-	-	RNAV 1 (1)
	TF	OT552	-	230	230.5	5.9	-	-	-	-	RNAV 1 (1)
	TF	OTKUR	-	195	195.2	17.2	-	4000	-	-	RNAV 1 (1)