

RNP Y RW21													
RMK	-											REF NAVAID :	
	Leg sequence	P/T	ID	Fly Over	Direction MAG °	Direction True °	Distance (NM or nmin)	Turn	MMM altitude (FL or AMSL ft)	MAX altitude (FL or AMSL ft)	MAX IAS (kt)	vertical angle (°) / TCH (m)	Nav Spec
INA OLALU	IF	OLALU	-	-	-	-	-	-	2800	-	210	-	RNP APCH
	TF	IOU21	-	114	114.6	5.0	R	2000	-	210	-	-	RNP APCH
INA NUVNU	IF	NUVNU	-	-	-	-	-	-	2800	-	210	-	RNP APCH
	TF	IOU21	-	205	205.1	5.0	-	2000	-	210	-	-	RNP APCH
INA ENOBU	IF	ENOBU	-	-	-	-	-	-	2800	-	210	-	RNP APCH
	TF	IOU21	-	295	295.6	5.0	L	2000	-	210	-	-	RNP APCH
APCH	TF	FOU21	-	205	205.1	4.0	-	2000	2000	-	-	-	RNP APCH
	TF	RW21	Yes	205	205.1	4.8	-	-	-	-	-	-3.0° / 15	RNP APCH
	TF	OU504	Yes	205	205.1	2.4	-	-	-	-	-	-	RNP APCH
	DF	ENOBU	-	-	-	-	L	-	-	210	-	-	RNP APCH
HLDG	-	ENOBU	-	-	-	-	-	-	-	-	-	-	-