

RNP RWY 32												
RMK	MAG VAR 2020 0.1° E						Ref NAVAID :					
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	Nav Spec
HLDG	-	ARNEV	-	-	-	-	-	-	-	-	-	-
INA ARNEV	IF	ARNEV	-	-	-	-	-	2100	-	195	-	RNP APCH
	TF	IOV32	-	233	232.9	5.0	-	2000	-	-	-	RNP APCH
INA BIRSO	IF	BIRSO	-	-	-	-	-	2200	-	230	-	RNP APCH
	TF	IOV32	-	322	322.5	5.0	-	2000	-	-	-	RNP APCH
INA OTLOV	IF	OTLOV	-	-	-	-	-	2100	-	210	-	RNP APCH
	TF	IOV32	-	052	051.9	5.0	-	2000	-	-	-	RNP APCH
	IF	IOV32	-	-	-	-	-	2000	-	-	-	RNP APCH
	TF	FOV32	-	322	322.4	4.6	-	2000	2000	-	-	RNP APCH
APCH	TF	RW32	Y	322	322.4	5.1	-	370	370	-	-3.0° / 15	RNP APCH
	TF	OV401	Y	322	322.3	4.0	-	-	-	-	-	RNP APCH
	DF	ARNEV	-	-	-	-	R	2100	-	195	-	RNP APCH