

PARIS LE BOURGET

PRECODING (GNSS) INA RNAV VEBEK 7W / OKABO 7W RWY 25
PRECODING (GNSS) INA RNAV BANOX 7W / MOPAR 7W RWY 25
PRECODING (GNSS) INA RNAV MOBRO 7W RWY 25

RMK	INA RNAV (GNSS ou / or DME / DME) RWY 25											
	(1) Sur instruction ATC uniquement / Only on ATC clearance.						MAG VAR 2020 1.0°E					REF NAVAID :
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MMM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Vertical angle (°) / TCH (m)	NAV Spec
HLDG	-	LORNI	-	-	-	-	-	-	-	-	-	-
HLDG	-	OKIPA	-	-	-	-	-	-	-	-	-	-
HLDG	-	BANOX	-	-	-	-	-	-	-	-	-	-
HLDG	-	MOPAR	-	-	-	-	-	-	-	-	-	-
INA	IF	VEBEK	-	-	-	-	-	FL110	FL110	250	-	RNAV 1
VEBEK 7W	TF	CTL	-	207	207.9	8.9	-	-	-	-	-	RNAV 1
	TF	PB510	-	224	224.9	7.9	-	-	-	-	-	RNAV 1
	FM	-	-	224	-	-	-	-	-	-	-	-
INA	IF	OKABO	-	-	-	-	-	FL070	FL070	250	-	RNAV 1
OKABO 7W	TF	DOBIK	-	312	313.3	5.7	-	-	-	-	-	RNAV 1
	TF	LIRSO	-	338	339.3	6.2	-	-	-	-	-	RNAV 1
	TF	PB508	-	329	329.9	5.6	-	-	-	-	-	RNAV 1
	FM	-	-	329	-	-	-	-	-	-	-	-
INA	IF	BANOX	-	-	-	-	-	FL070	FL070	250	-	RNAV 1
BANOX 7W	TF	PB502	-	043	043.8	15.4	-	-	-	-	-	RNAV 1
	TF	PB504	-	085	086.5	18.0	-	-	-	-	-	RNAV 1
	TF	PB506	-	073	074.3	10.7	-	-	-	-	-	RNAV 1
	FM	-	-	073	-	-	-	-	-	-	-	-
INA	IF	MOPAR	-	-	-	-	-	FL110	FL120	300	-	RNAV 1
MOPAR 7W	TF	PG534	-	093	093.9	24.8	-	-	-	-	-	RNAV 1
(1)	TF	CREIL	-	093	094.4	5.0	-	-	-	-	-	RNAV 1
	TF	PG536	-	099	100.1	8.0	-	-	-	-	-	RNAV 1
	FM	-	-	099	-	-	-	-	-	-	-	-
INA	IF	MOBRO	-	-	-	-	-	FL070	FL070	250	-	RNAV 1
MOBRO 7W	TF	BOV	-	092	092.9	21.4	-	-	-	-	-	RNAV 1
	TF	PG528	-	106	107.2	15.6	-	-	-	-	-	RNAV 1
	FM	-	-	106	-	-	-	-	-	-	-	-