

PRECODING (GNSS) INA RNAV VEBEK 7W / OKABO 7W RWY 27
PRECODING (GNSS) INA RNAV BANOX 7W / MOPAR 7W RWY 27
PRECODING (GNSS) INA RNAV MOBRO 7W RWY 27

RMK	INA RNAV (GNSS ou / or DME / DME) RWY 27										REF NAVAID :		
	(1) Sur instruction ATC unquement / Only on ATC clearance.										Vertical angle (°) / TCH (m)	NAV Spec	
Leg sequence	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NIM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	MAG VAR 2020 1.0°E		
HLDG	-	LORNI	-	-	-	-	-	-	-	-	-	-	-
HLDG	-	OKIPA	-	-	-	-	-	-	-	-	-	-	-
HLDG	-	BANOX	-	-	-	-	-	-	-	-	-	-	-
HLDG	-	MOPAR	-	-	-	-	-	-	-	-	-	-	-
INA VEBEK 7W	IF	VEBEK	-	-	-	-	-	FL110	FL110	250	-	-	RNAV 1
	TF	CTL	-	207	207.9	8.9	-	-	-	-	-	-	RNAV 1
	TF	PB510	-	224	224.9	7.9	-	-	-	-	-	-	RNAV 1
	FM	-	-	224	-	-	-	-	-	-	-	-	-
INA OKABO 7W	IF	OKABO	-	-	-	-	-	FL070	FL070	250	-	-	RNAV 1
	TF	DOBIK	-	312	313.3	5.7	-	-	-	-	-	-	RNAV 1
	TF	LIRSO	-	338	339.3	6.2	-	-	-	-	-	-	RNAV 1
	TF	PB508	-	329	329.9	5.6	-	-	-	-	-	-	RNAV 1
	FM	-	-	329	-	-	-	-	-	-	-	-	-
	IF	BANOX	-	-	-	-	-	FL070	FL070	250	-	-	RNAV 1
INA BANOX 7W	TF	PB502	-	043	043.8	15.4	-	-	-	-	-	-	RNAV 1
	TF	PB504	-	085	086.5	18.0	-	-	-	-	-	-	RNAV 1
	TF	PB506	-	073	074.3	10.7	-	-	-	-	-	-	RNAV 1
	FM	-	-	073	-	-	-	-	-	-	-	-	-
	IF	MOPAR	-	-	-	-	-	FL110	FL120	300	-	-	RNAV 1
INA MOPAR 7W (1)	TF	PG534	-	093	093.9	24.8	-	-	-	-	-	-	RNAV 1
	TF	CREIL	-	093	094.4	5.0	-	-	-	-	-	-	RNAV 1
	TF	PG536	-	099	100.1	8.0	-	-	-	-	-	-	RNAV 1
	FM	-	-	099	-	-	-	-	-	-	-	-	-
INA MOBRO 7W	IF	MOBRO	-	-	-	-	-	FL070	FL070	250	-	-	RNAV 1
	TF	BOV	-	092	092.9	21.4	-	-	-	-	-	-	RNAV 1
	TF	PG528	-	106	107.2	15.6	-	-	-	-	-	-	RNAV 1
	FM	-	-	106	-	-	-	-	-	-	-	-	-