

**PARIS CHARLES DE GAULLE**  
**Réacteurs (R) et hélices (H) / Jets (R) and propellers (H)**  
**SID RNAV RWY 27L - 27R**  
Protégés pour / Protected for CAT A, B, C, D

SID RNAV RWY 27L - 27R											
RMK	GNSS ou/ou DME/DME						MAG VAR 2020 1,1°E			Ref NAVAID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Nav Spec
<b>LATRA 5Z</b>											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	262.5	-	-	-	-	-	-
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	RNAV 1
-	CF	PON	-	271	272.0	-	-	-	-	-	RNAV 1
-	TF	DEROL	-	172	172.9	25.3	-	-	-	-	RNAV 1
-	TF	LALUX	-	152	153.4	26.2	-	-	-	-	RNAV 1
-	TF	LATRA	-	159	160.4	12.9	-	-	-	280	RNAV 1
<b>OKASI 5Z</b>											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	262.5	-	-	-	-	-	-
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	RNAV 1
-	CF	PON	-	271	272.0	-	-	-	-	-	RNAV 1
-	TF	PG289	-	159	160.3	17.7	-	-	-	-	RNAV 1
-	TF	DOPAP	-	161	162.2	7.3	-	-	-	-	RNAV 1
-	TF	ODEBU	-	148	148.7	29.5	-	-	-	-	RNAV 1
-	TF	OKASI	-	152	152.8	13.3	-	-	-	280	RNAV 1
<b>PILUL 5Z</b>											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	262.5	-	-	-	-	-	-
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	RNAV 1
-	CF	PON	-	271	272.0	-	-	-	-	-	RNAV 1
-	TF	PG289	-	159	160.3	17.7	-	-	-	-	RNAV 1
-	TF	OXCEL	-	122	123.3	9.7	-	-	-	-	RNAV 1
-	TF	PEKIM	-	146	147.3	32.3	-	-	-	-	RNAV 1
-	TF	PILUL	-	141	142.2	14.6	-	-	-	280	RNAV 1
<b>DORDI 5A</b>											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG273	-	273	274.0	-	-	-	-	-	RNAV 1
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	RNAV 1
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	RNAV 1
-	TF	DORDI	-	151	152.2	34.6	-	-	-	-	RNAV 1
<b>OLZOM 5A</b>											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG273	-	273	274.0	-	-	-	-	-	RNAV 1
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	RNAV 1
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	RNAV 1
-	TF	OLZOM	-	187	188.3	34.9	-	-	-	-	RNAV 1
<b>MONOT 5A</b>											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG273	-	273	274.0	-	-	-	-	-	RNAV 1
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	RNAV 1
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	RNAV 1
-	TF	PG277	-	187	188.3	21.8	-	-	-	-	RNAV 1
-	TF	MONOT	-	160	161.2	18.2	-	-	-	-	RNAV 1
<b>DORDI 5D</b>											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG273	-	273	274.0	-	-	-	-	-	RNAV 1
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	RNAV 1
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	RNAV 1
-	TF	DORDI	-	151	152.2	34.6	-	-	-	-	RNAV 1
<b>OLZOM 5D</b>											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG273	-	273	274.0	-	-	-	-	-	RNAV 1
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	RNAV 1
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	RNAV 1
-	TF	OLZOM	-	187	188.3	34.9	-	-	-	-	RNAV 1