

PARIS CHARLES DE GAULLE
Réacteurs (R) et hélices (H) / Jets (R) and propellers (H)
SID RNAV RWY 27L - 27R
Protégés pour / Protected for CAT A, B, C, D

SID RNAV RWY 27L - 27R											
RMK	GNSS ou/ou DME/DME						MAG VAR 2020 1,1°E			Ref NAVAIID : BT	
Procedure Identification	Path Terminator	Waypoint Identification	Fly Over	Direction MAG (°)	Direction True (°)	Distance (NM)	Turn direction	MNM Altitude (FL or AMSL ft)	MAX Altitude (FL or AMSL ft)	MAX IAS (kt)	Nav Spec
MONOT 5D											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG273	-	273	274.0	-	-	-	-	-	RNAV 1
-	TF	PG275	-	190	190.7	9.1	-	-	-	220	RNAV 1
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	RNAV 1
-	TF	MONOT	-	175	176.0	38.9	-	-	-	-	RNAV 1
DORDI 5Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	262.5	-	-	-	-	-	-
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	RNAV 1
-	CF	PON	-	271	272.0	-	-	-	-	-	RNAV 1
-	TF	PG275	-	190	190.8	12.3	-	-	-	220	RNAV 1
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	RNAV 1
-	TF	DORDI	-	151	152.2	34.6	-	-	-	-	RNAV 1
OLZOM 5Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	262.5	-	-	-	-	-	-
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	RNAV 1
-	CF	PON	-	271	272.0	-	-	-	-	-	RNAV 1
-	TF	PG275	-	190	190.8	12.3	-	-	-	220	RNAV 1
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	RNAV 1
-	TF	OLZOM	-	187	188.3	34.9	-	-	-	-	RNAV 1
MONOT 5Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	262.5	-	-	-	-	-	-
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	RNAV 1
-	CF	PON	-	271	272.0	-	-	-	-	-	RNAV 1
-	TF	PG275	-	190	190.8	12.3	-	-	-	220	RNAV 1
-	TF	OXCEL	-	120	121.2	19.1	-	-	-	-	RNAV 1
-	TF	PG277	-	187	188.3	21.8	-	-	-	-	RNAV 1
-	TF	MONOT	-	160	161.2	18.2	-	-	-	-	RNAV 1
LGL 5A											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG280	Y	273	274.5	-	-	-	-	-	RNAV 1
-	DF	PG284	-	-	-	-	-	-	-	-	RNAV 1
-	TF	EVX	-	262	263.2	16.2	-	-	-	-	RNAV 1
-	TF	LESGA	-	241	242.5	18.6	-	-	-	-	RNAV 1
-	TF	LGL	-	241	241.8	12.4	-	-	-	-	RNAV 1
EVX 5A											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG280	Y	273	274.5	-	-	-	-	-	RNAV 1
-	DF	PG284	-	-	-	-	-	-	-	-	RNAV 1
-	TF	EVX	-	262	263.2	16.2	-	-	-	-	RNAV 1
LGL 5D											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG280	Y	273	274.5	-	-	-	-	-	RNAV 1
-	DF	PG284	-	-	-	-	-	-	-	-	RNAV 1
-	TF	EVX	-	262	263.2	16.2	-	-	-	-	RNAV 1
-	TF	LESGA	-	241	242.5	18.6	-	-	-	-	RNAV 1
-	TF	LGL	-	241	241.8	12.4	-	-	-	-	RNAV 1
EVX 5D											
RWY27L	CF	PG271	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	261.6	-	-	-	-	-	-
-	TF	PG272	Y	264	265.3	3.3	-	-	-	-	RNAV 1
-	CF	PG280	Y	273	274.5	-	-	-	-	-	RNAV 1
-	DF	PG284	-	-	-	-	-	-	-	-	RNAV 1
-	TF	EVX	-	262	263.2	16.2	-	-	-	-	RNAV 1
LGL 5Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	262.5	-	-	-	-	-	-
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	RNAV 1
-	CF	PON	-	271	272.2	-	-	-	-	-	RNAV 1
-	TF	EVX	-	262	263.2	32.4	-	-	-	-	RNAV 1
-	TF	LESGA	-	241	242.5	18.6	-	-	-	-	RNAV 1
-	TF	LGL	-	241	241.8	12.4	-	-	-	-	RNAV 1
EVX 5Z											
RWY27L	CF	PG270	-	264	265.3	-	-	-	-	-	RNAV 1
RWY27R			-	261	262.5	-	-	-	-	-	-
-	TF	PG290	Y	327	327.9	3.8	-	-	-	-	RNAV 1
-	CF	PON	-	271	272.2	-	-	-	-	-	RNAV 1
-	TF	EVX	-	262	263.2	32.4	-	-	-	-	RNAV 1